


- NOTES:**
1. ALL FOUNDATION LOCATIONS SHALL BE DETERMINED IN FIELD BY TRAFFIC DIVISION AT TIME OF CONSTRUCTION.
  2. FOUNDATION TOP SHALL HAVE SQUARE EDGES AND BE FINISHED ON ALL SIDES.
  3. CABINET ANCHORS ARE WEDGE ANCHORS, 4 PER CABINET, 1/2" X 4 1/2" STAINLESS STEEL (#304) FULL THREADED.
- ① 3" FROM HIGHPOINT OF FINISHED SIDEWALK GRADE,  
4" FROM HIGHPOINT OF FINISHED BOULEVARD GRADE.
- ② PROVIDE PROTECTIVE BUSHINGS ON ALL CONDUITS
- ③ ELECTRICAL CONDUITS AS SPECIFIED
- ④ KEEP SERVICE FEED TO LEFT OF BARRIER

NO SCALE

	<b>MINNEAPOLIS</b> DEPARTMENT OF PUBLIC WORKS		FOUNDATION - SIGNAL  CONTROLLER CABINET TYPE "P" AND ST. LIGHT / DUAL SERVICE CABINET	STANDARD PLATE NO. TRAF-1071-R1
	DRAWN: CLK  APPROVED: DRP	DATE: 9/14/12  DATE: 9/14/12	REFERENCE PLATE: TRAF-3483, TRAF-3487	