SECONDARY SIGNAL HEADS

NOTES: 1.*SIGNAL HEAD WIRING SHALL PROVIDE 1-NEUTRAL & 1 SPARE PER HEAD **ASSEMBLY**

2. WHEN SPACE EXISTS ON SINGLE TERMINAL **BLOCK ALL HEAD WIRES SHALL BE TERMINATED FOR ARROW AND PED** MOVEMENTS.

3. WIRE NUT SPLICE



- 12/C RED/BLK Ø4 OR Ø8 -12/C ORN/BLK LT ARROWS L - 12/C BLU/BLK


- 12/C BLK/WHT Ø8 PED - 12/C BLK

- 12/C YEL Ø6 PED - 12/C YEL/BLK

NEU-12/C WHT -

EQ.G-12/C GRN -

1/2" X 1" GRD CLAMP



TO NEXT SIGNAL IF REQ'D

SIGNAL & PED HEAD WIRES-1/C

#14 XHHW-2 QTY & QUALITY AS

DIRECTED BY THE ENGINEER.

*BLK-

RED

BLU

GRN

ORN BLU.

YEL

BLK BLK

YEL .

*WHT RED

SPECIFIED. TAPE TOGETHER AS

NO SCALE

Ø2 OR Ø6

Ø4 OR Ø8

Ø8 PED

- Ø6 PED

LT ARROWS

LT ARROWS



MINNEAPOLIS DEPARTMENT OF PUBLIC WORKS

CONTROLLER

DRAWN: LPK DATE: 1/1/11 APPROVED: DRP DATE: 1/1/11

PEDESTAL - ODD PHASES

STANDARD PLATE NO. TRAF-1584

WIRING - SIGNAL